

AZ-KBXZW2MP

K-Series

Full HD IP Box Camera

MOTORIZED LENS



Key Features

- Full HD 2.0 Megapixel IP Box Camera
- Auto Exposure, Auto White Balance
- Triple Stream (H.264, MPEG4, MJPEG)
- True WDR (120db)
- True Day & Night
- Easy Install : Zero Configuration, Discovery, PoE
- Event Boosting, FTP Image upload, Web Casting, Open VPN, QoS, IP Filtering
- Support: Onvif Profile S
- Privacy Masking, Support progressive scan
- Cross Web Browsing(IE, Safari, Firefox, Chrome)
- Event Buffering
- Support SD Card Up to 32GB

Technical Specification

AZ-KBXZW2MP	
VIDEO	
Image Device	1/2.8" SONY Exmor CMOS Sensor 2.0 Megapixel
Total Pixel	1952(H)x1236(V)
Min. Illumination	Color 0.4 Lux@F1.2 50IRE, BW: 0.01 LUX@ F1.2 50IRE (IR ON)
Video Compression	H.264, MJPEG
Bitrate Control	CVBR, VBR
Security	Multi User Authority, IP Filtering, HTTPS, SSL
Resolution	1920x1080, 1280x1024, 1280x720/960, 1024x768, 704x480/576, 640x360/480, 320x240
Frame Rate	Max. 50/60fps@Full-HD
Image Effect	Flip, Mirror, Aisle
Shutter Speed	Auto(1/10,000~1sec), Manual
Video Analytics	DIS, Defog, Face Detection, Tampering, Line Detector, Field Detector (Built-in VCA)
EXTERNAL IN/OUT	
Video Composite Out	3.5mm Stereo Jack
Audio	1 Input, 1 Output(3.5mm Stereo Jack)
Alarm	1 Input, 1 Output(Terminal Block)
Ethernet	RJ-45(10/100Base-T)
RS485	Yes
OPERATIONAL	
Noise Reduction	2DNR, 3DNR
Digital Zoom	Yes(ROI)
WDR	True WDR(120dB)
Day and Night Mode	True Day & Night(Auto, Day, Night)
Motion Detection	16 Programmable Area (Include Area 8, Exclude Area 8)
Privacy Mask	8 Programmable Zone
Event Notification	E-mail, FTP, Notification Server, XML Notification, Audio Alert, AIHM
Network Time Sync	NTP Server, Synchronized Computer, Manual
SD Recording Mode	Event, Continuous
Auto Recovery	Backup, Restore
Audio Compression	G.711
Audio Streaming	2 Way
Streaming	50/60fps(Dual Stream : H.264x1, MJPEGx1), 25/30fps(Triple Stream : H.264x2, MJPEGx1), Advanced VCA only 25/30fps
LENS	
Motorized Lens Control	Yes
Lens	C/CS Mount

AZ-KBXZW2MP

K-Series

Full HD IP Box Camera

ANALOG CAMERA

AHD CAMERA

IP CAMERA

DVR

NVR

Technical Specification

AZ-KBXZW2MP	
NETWORK	
Protocol	IPv4/IPv6, Manual, TCP/IP, UDP, HTTP, RTP, RTSP, NTP, DHCP, SMTP, DDNS, HTTPS, RTCP, FTP
Max. User Connection	Live : 10 Users, Playback : 3 Users
API Support	Open API, Onvif Compliance
Mobile Support	Five HD(Android, iOS)
ENVIRONMENTAL	
Operating Temperature	-10° C ~ 50° C
Operating Humidity	0~90% RH (Non-Condensing)
ELECTRICAL	
Power Supply	12VDC, 24VAC
PoE	Yes
MECHANICAL	
Dimension (mm)	81.6(W)x68(H)x123(L)mm
Net Weight	365g